

Dual Output Digital Audio Converter

PARTS SUPPLIED:

Audio Converter (1)


Power Supply (1)

Features

- 1.Supports two-way conversion: Coaxial to Toslink or Toslink to Coaxial.
- 2.Supports multichannel audio.
- 3.Select one input from Coaxial or Toslink input ports, and send S/PDIF audio signal to both Coaxial and Toslink output ports simultaneously.

Specifications

1. Input: 1 x Coaxial RCA Jack & 1 x Toslink (optical fiber) port
- 2.Output: 1 x Coaxial RCA Jack & 1 x Toslink (optical fiber) port
- 3.Coaxial RCA Input impedance: 75 ohms
- 4.DC Input Connector:5.5 x 2.1 x 9.5 mm
- 5.DC Input Voltage/Polarity: 12V /Center positive
- 6.Dimensions:88.4L x 64.5W x 29H mm
- 7.Weight: 54 g (adaptor not included)



Dual Output Digital Audio Converter

PARTS SUPPLIED:

Audio Converter (1)

Power Supply (1)

Features

- 1.Supports two-way conversion: Coaxial to Toslink or Toslink to Coaxial.
- 2.Supports multichannel audio.
- 3.Select one input from Coaxial or Toslink input ports, and send S/PDIF audio signal to both Coaxial and Toslink output ports simultaneously.

Specifications

1. Input: 1 x Coaxial RCA Jack & 1 x Toslink (optical fiber) port
- 2.Output: 1 x Coaxial RCA Jack & 1 x Toslink (optical fiber) port
- 3.Coaxial RCA Input impedance: 75 ohms
- 4.DC Input Connector:5.5 x 2.1 x 9.5 mm
- 5.DC Input Voltage/Polarity: 12V /Center positive
- 6.Dimensions:88.4L x 64.5W x 29H mm
- 7.Weight: 54 g (adaptor not included)

